

## GAGE229/0546-80-35

## High-precision Bi-telecentric Lens

- · Large CCD size, high resolution imaging system design;
- FOV from 26mm upto 300mm;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.



| Optical Specifications             |           |  |
|------------------------------------|-----------|--|
| Magnification (x)                  | 0.545     |  |
| Object Field of View (Фтт)         | 80        |  |
| Working Distance (mm)              | 230±2     |  |
| Max Sensor Size (Фmm)              | 44 (35mm) |  |
| Best Aperture (F/#)                | 17.1      |  |
| Telecentricity typical (max) (deg) | <0.1      |  |
| Distortion typical (max) (%)       | <0.1      |  |
| MTF30 (lp/mm)                      | >65       |  |
| Depth of Field (mm)                | ±4        |  |
| Length of I/O (mm)                 | 532.7     |  |

| Field of View (mm × mm)   |                    |  |
|---------------------------|--------------------|--|
| 36.17x24.11w ith KAI29050 | 66.3x44.2          |  |
| Mechanical Specifications |                    |  |
| Mount                     | F                  |  |
| Length (mm)               | 256.2              |  |
| Compatible Lighting       |                    |  |
| Telecentric LED Lighting  | VCL-80-xW-y        |  |
|                           | Beam Diameter 80mm |  |

## Notes:

- 1.Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2.Length of I/O = WD + Length + Back Focal Length.

